

TMD DIGGER DERRICK

TMD-4045T/TMD-4050T/TMD-4055T/TMD-4060T



VERSALIFT

VERSALIFT is a leading manufacturer of bucket trucks, digger derricks, aerial lifts and other specialty equipment for power generation, transmission and distribution, investor-owned utility, telecommunications, light and sign, and tree care industries. Working with co-ops, municipalities, government agencies and corporations through its global network of facilities and family of dealers, the company employs nearly 800 associates worldwide.

7601 Imperial Drive, Waco, Texas 76712 | 254-399-2100 | www.VERSALIFT.com

TMD T SERIES

Full Pressure Hydraulic Digger Derrick



General Specifications	TMD-4045T	TMD-4050T	TMD-4055T	TMD-4060T
Maximum Capacity	30500 lbs (13850 kg)	30500 lb (13850 kg)	30000 lb (13600 kg)	29200 lb (13250 kg)
Capacity at 10ft Radius	18100 lbs (8200 kg)	17700 lb (8050 kg)	17100 lb (7750 kg)	16600 lb (7550 kg)
HORIZONTAL REACH				
Horizontal Reach (B1)	18.9 ft (5.8 m)	20.6 ft (6.3 m)	22.2 ft (6.8 m)	23.9 ft (7.3 m)
Horizontal Reach (B2)	27.9 ft (8.5 m)	31.2 ft (9.5 m)	34.6 ft (10.5 m)	37.9 ft (11.6 m)
Horizontal Reach (B3)	35.2 ft (10.7 m)	40.2 ft (12.3 m)	45.2 ft (13.8 m)	50.2 ft (15.3 m)
SHEAVE HEIGHT				
Sheave Height (A1)	29.3 ft (8.9 m)	31.0 ft (9.4 m)	32.6 ft (9.9 m)	34.2 ft (10.4 m)
Sheave Height (A2)	38.2 ft (11.6 m)	41.5 ft (12.6 m)	44.7 ft (13.6 m)	48.0 ft (14.6 m)
Sheave Height (A3)	45.4 ft (13.8 m)	50.3 ft (15.3 m)	55.2 ft (16.8 m)	60.2 ft (18.3 m)
LOAD RADIUS				
Load Radius (R1)	4.3 ft (1.3 m)	4.6 ft (1.4 m)	4.9 ft (1.5 m)	5.2 ft (1.6 m)
Load Radius (R2)	5.9 ft (1.8 m)	6.4 ft (2.0 m)	7.0 ft (2.1 m)	7.6 ft (2.3 m)
Load Radius (R3)	7.1 ft (2.2 m)	8.0 ft (2.4 m)	8.9 ft (2.7 m)	9.7 ft (3.0 m)
DIG RADIUS				
Dig Radius (S1)	16.4 ft (5.0 m)	18.1 ft (5.5 m)	19.7 ft (6.0 m)	21.4 ft (6.5 m)
Dig Radius (S2)	25.4 ft (7.7 m)	28.8 ft (8.8 m)	32.1 ft (9.8 m)	35.4 ft (10.8 m)

OPTIONS:

- Fiberglass Platform
- Liners Available
- Hard-Wired Electric/Hydraulic Lower Controls
- Radio Remote Controls
- Full Pressure Upper Controls with Boom Sequencing
- Various Single Stick Handles
 - Standard VERSALIFT Handle
 - T-Handle
- 5 FT Underslung Jib
- Hydraulic Tool Power Outlets
- Multi-Part Line Components
- Various Types of Outriggers
- Various Augers
- Various Digger Drives
- Left-Hand Riding Seat
- Lower Boom Stow Limit
- Riding Seat Access Ladder

NOTE:

1. Specifications may vary without prior notice
2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload.